

BB4GL RDBMS-specific Compiler Includes

IBP.SPEC.....	Description.....
@D	goes back to AccuTerm default font
ABSS	Multivalued ABS()
ADDS	Multivalued ADD function
ANDS	Multivalued AND function
APR93	internal Purveyor use
ASSIGNED	Compatibility for ASSIGNED()
AUG92	
AVERAGE	produces averages on the break lines when TOTALed
B.ROUND	Banker's rounding
B.ROUNDS	Banker's rounding - multivalued
BASICTYPE	compiler compaibility statement
BASICTYPEU	compatibility w U2
BB.TCL.AVERAGE	produces averages on the break lines when TOTALed
BB.TCL.FUNCTIONS	functions appropriate for this RDBMS
BB.TCL.REMOVE1	for future use
BB.TCL.REMOVE2	for future use
BFORMAT.B	Does laser BOLD for print jobs
BFORMAT.B.B	Does laser BOLD for print jobs on the break lines
BFORMAT.B.BLACK	Does laser COLOR for print jobs on the break lines
BFORMAT.B.BLUE	Does laser COLOR for print jobs on the break lines
BFORMAT.B.CYAN	Does laser COLOR for print jobs on the break lines
BFORMAT.B.GREEN	Does laser COLOR for print jobs on the break lines
BFORMAT.B.I	Does laser ITALICS for print jobs on the break lines
BFORMAT.B.MAGENTA	Does laser COLOR for print jobs on the break lines
BFORMAT.B.RED	Does laser COLOR for print jobs on the break lines
BFORMAT.B.U	Does laser UNDERLINE for print jobs on the break lines
BFORMAT.B.YELLOW	Does laser COLOR for print jobs on the break lines
BFORMAT.BLACK	Does laser COLOR for print jobs
BFORMAT.BLUE	Does laser COLOR for print jobs
BFORMAT.CYAN	Does laser COLOR for print jobs
BFORMAT.GREEN	Does laser COLOR for print jobs
BFORMAT.I	Does laser ITALICS for print jobs
BFORMAT.MAGENTA	Does laser COLOR for print jobs
BFORMAT.RED	Does laser COLOR for print jobs
BFORMAT.U	Does laser UNDERLINE for print jobs
BFORMAT.YELLOW	Does laser COLOR for print jobs
BREAKOFFVERB	Break key off verb
BREAKONVERB	Break key on verb
BRNO	internal Purveyor use
C.USER	
CAPTURING.OFF	hushes terminal output with EXECUTE CAPTURING
CAPTURING.ON	turns off CAPTURING terminal output suppression
CATS	Multivalued CONCATENATION function
CHARS	Multivalued CHAR()
COMPATIBLE	for compiler compatibility w other systems
CONVERT	mimics CONVERT function
COUNTS	Multivalued COUNT
DCOUNTS	Multivalued DCOUNT

DEC92	internal Purveyor use
DIVS	Multivalued DIVISION function
DOWNCASE	converts to lower case
DS.COMMONS	internal Purveyor use
E.INMAT	internal use w E editor
EQS	Multivalued equals
EXEC	
EXEC.LEVEL	returns the execution level
EXEC.SUB	for internal use in UTIL EXEC.SUB
EXPS	Multivalued EXPONENTIATION function
F.YTD.EXP.\$GP	internal Purveyor use
F.YTD.EXP.\$SLS	internal Purveyor use
F.YTD.EXP.CASES	internal Purveyor use
F.YTD.EXP.DMD	internal Purveyor use
F.YTD.EXP.LY.\$GP	internal Purveyor use
F.YTD.EXP.LY.\$SLS	internal Purveyor use
F.YTD.EXP.LY.DMD	internal Purveyor use
F.YTD.EXP.LY.SLS	Internal Purveyor use
F.YTD.EXP.SLS	internal Purveyor use
FCORR.WIDTH	
FEB93	internal Purveyor use
FIELDS	Same as FIELD(WHOLE,DELIM,BFLD,HOW.MANY) on many d atabase O/S
FOLD	Splits a string into an array using spaces
FOLDD	Splits a string into an array using spaces
FOLDS	multi-valued FOLD
FUNCTIONS	functions appropriate for this RDBMS
GES	Multivalued greater than or equals
GET.COMP.LISTS	internal use with UTIL EXEC.SUB
GETONE	
GETONE2	unedited single character input, but translates AN SI terminals
GRPSTR	Replaces a field with a string
GTS	Multivalued greater than or equals
I.AUG92	internal Purveyor use
I.DEC92	internal Purveyor use
I.JUL92	internal Purveyor use
I.JUN92	internal Purveyor use
I.MAY92	internal Purveyor use
I.NOV92	internal Purveyor use
I.OCT92	internal Purveyor use
I.SEP92	internal Purveyor use
ICONVS	Multivalued ICONV
ICV	Validates fields in data entry
IDX	SIMILAR TO PICK INDEX FUNCTION, BUT WILL ACCEPT GL OBAL CHARACTER.
IDXS	SIMILAR TO PICK INDEX FUNCTION, BUT WILL ACCEPT GL OBAL CHARACTER.
IFS	Multivalued IF function
INDEXS	Multivalued INDEX function
INVSTATUS	internal Purveyor use
ISNULLS	Multivalued check for null values
JAN93	
JOIN.LIST	joins lists, for internal use

JUL92	internal Purveyor use
JUN92	internal Purveyor use
LAYR	internal Purveyor use
LENS	Multivalued LEN function
LES	Multivalued less than or equals
LIST-LOCKS	
LIST.LOCKS	item locks listing
LOCKINGPORT	determines port which is locking current user
LOWER	lowers delimiters
LTS	Multivalued less than
MAR93	internal Purveyor use
MATCHESES	Multivalued MATCHES PATTERN
MAXIMUM	Maximum function
MAY92	internal Purveyor use
MAY93	internal Purveyor use
MCP	Similar to the Pick MCP conversion, but it deletes bad chars rather than changing them to periods
MCP.INS	for UTIL MCP, internal use
MCT	CONVERTS A LINE OF TEST FROM "JOHN T. SMITH" TO "John T. Smith"
MINIMUM	minimum function
MODS	Multivalued MOD function
MULS	Multivalued MULTIPLICATION function
MULTS	Multivalued MULTIPLICATION function
NEG	returns the negative of the value
NEGS	Multivalued NEG function
NES	Multivalued not equals
NOTS	Multivalued # function
NOV92	internal Purveyor use
NUMS	Multivalued NUM()
OCONVS	Multivalued OCONV
OCT92	internal Purveyor use
OCV	uses dictionaries to perform output conversions for or database integrity
ONPO	internal Purveyor use
ORS	Multivalued OR function
PERCENT	produces percentages on the break lines when TOTAL ed
PGM.NAME	determines program name from tcl sentence
PROC.BREAKOFFVERB	
PROC.BREAKONVERB	
PROC.EXEC.1	internal use with Proc execute statements
PS.CHECK	internal use
RAISE	raises delimiters
RCL.FUNCTIONS	generic function handler for I-descriptors in BB.TCL, for future use
RCL.INTERPRET	include for B-correlatives
REP.COST.ORDER	
REPLVALUE	internal Purveyor use
RETURN.B	B-correlative RETURN clause
SAVE.COMP.LIST	internal use with UTIL EXEC.SUB
SAVE.SCROLL	internal use to UTIL SCROLL.ANY
SCHAR	Unedited single character input w/o translation
SELECTTEST	Determines whether a select list is present

SEP92	internal Purveyor use
SEQS	Multivalued SEQ()
SET.CONV1	internal use
SINGLECHAR	single character unedited input
SINGLECHAR2	single character unedited input
SOUNDEXS	Multivalued SOUNDEX()
SPACES	Multivalued SPACE()
SPOOLEROPTION	determines spooler options
SPOOLQ.OFF	SPOOLER queue number suppressed
SPOOLQ.ON	SPOOLQ suppress OFF
SSOUNDEX	ADD A SET OF SOUNDEX INDICES FOR A DESCRIPTION.
SSOUNDEXS	Multivalued SSOUNDEX()
SSUM	SUBROUTINE TO SUM SUBVALUES INTO VALUES, VALUES INTO ATTRIBUTES, AND ATTRIBUTES INTO ITEMS, ONE STEP PER CALL.
STACKED.DATA	Returns whether there is data stacked
STACKER.SELECT	internal use in UTIL STACKER and RRR
START.BP	can be used when starting programs, see also UTIL START.BP
STRS	Multivalued STR function
SUB.LIST.HANDLER.ITYPE	for internal use with UTIL SUB.LIST.HANDLER, use MD LIST.HANDLER in TCL
SUB.LIST.HANDLER.READ	used w UTIL SUB.LIST.HANDLER, use MD LIST.HANDLER in TCL
SUB.NUM.ATTS	B-corr that returns the number of attributes in an item.
SUBS	Multivalued SUBTRACTION function
TA.STATUS	Type ahead status
TA.TEST	Type ahead status
TANDEM.SETUP	Figures out the Tandem port
TCL.SENTENCE	Sentence which invokes program
TERMTYPE	Terminal type
TOTALREPLVALUE	internal Purveyor use
TRANS	file translation for BB.TCL Access
TRANS.ANSI	translates escape sequences in BB.IBP.SPEC GETONE for ANSI term types
TRAP.INTERRUPT	Interrupt trapping
UNASSIGNED	Compatibility for UNASSIGNED()
UPCASE	converts to upper case
VAR.ASSIGNED	returns assigned status of variable
VAR.UNASSIGNED	Returns variable unassigned status
WHO	WHO related variable assignments
WORDPROC.VERB	word processing verb
XORS	Multivalued OR function
YTD.EXP	internal Purveyor use
YTD.EXP.\$GP	internal Purveyor use
YTD.EXP.\$SLS	internal Purveyor use
YTD.EXP.CASES	internal Purveyor use
YTD.EXP.DMD	internal Purveyor use
YTD.EXP.LY.\$GP	internal Purveyor use
YTD.EXP.LY.\$SLS	internal Purveyor use
YTD.EXP.LY.DMD	internal Purveyor use
YTD.EXP.LY.SLS	internal Purveyor use
YTD.EXP.SLS	Internal Purveyor use